

HL265/HL275

all stainless steel checkweighers - protection where you need it



stainless steel scales for the food industry

Avery Berkel

models HL265 & HL275 checkweighers

- protection where you need it

The **HL265** and **HL275** are a series of bench checkweighers particularly suited to the food industry. Capacities range from 1 kg up to 90 kg, with EU Trade Approval to 3000 divisions on the **HL265**, or non-approved to 6000 divisions on either model.

Protection where you need it -

- ◆ **In The Workplace** - The scale is fully stainless steel, including the load cell, and sealed to IP66 (NEMA 4X) for added protection in washdown environments.
- ◆ **In The Scale Base** - A 'Breakaway Load Transfer System' transfers shock loads and overloads away from the load cell, for added protection and reliability, giving up to 500% overload protection.
- ◆ **In the Pocket** - The rugged reliability comes to you at a very competitive price. A rapid-response display combines with the scale's superior accuracy to minimise your 'give-away'.



Specification

Capacity	*1 kg	3 kg	6 kg	15 kg	30 kg	45 kg	90 kg
Sensitivity							
Non-approved	0.2 g	0.5 g	1 g	2 g	5 g	10 g	20 g
†Approved	-	1 g	2 g	5 g	10 g	20 g	50 g
Pan size (mm) (W x D)	220 x 220			350 x 310		508 x 508	610 x 610

* Model HL275 only.

† Only model HL265 has approved specification.

- ◆ **Display type:** 7-segment LCD or LED.
- ◆ **Units:** kg, g, lbs, oz.
- ◆ **Displays:** **Model HL265:** 13 mm vacuum fluorescent or 17 mm LCD (essential if battery operation required). Three coloured LED's for Over/Under checkweighing.

Model HL275: 13 mm vacuum fluorescent. Multi-coloured 45-segment graphics display for Over/Under checkweighing.

- ◆ **Power Supply:** 110 or 240 volts AC.
- ◆ **Battery Option:** 12 V DC for LCD version of Model **HL265** only. With 30 hours battery life, 14 hour re-charge time. Power-preserving shut down and low battery warning.
- ◆ **Column Option:** Both models are available with either a low head (135 mm to centre of display) or a column-mounted head (310 mm to centre of display). Remote head versions are also available.
- ◆ **Data Output Option:** An RS232 or RS485 is available for all models.

Left: HL275 display illustrating Under, Accept & Over LCDs.

© Avery Berkel Limited 2001. All rights reserved. This publication is issued to provide outline information only which, unless agreed by Avery Berkel Limited in writing, may not be regarded as a representation relating to the products or services concerned. Avery Berkel Limited reserved the right to alter without notice the specification, design, price or conditions of supply of any product or service.

Your local distributor:



E mail: info@averyberkel.com
Internet: <http://www.averyberkel.com>

Foundry Lane, Smethwick,
West Midlands, England B66 2LP.
Tel: +44 (0)870 90 34343 Fax: +44 (0)870 90 50085